

# LINE INTERACTIVE UPS



## THE BEST SOLUTION FOR HOME & OFFICE

#### **FEATURES**

- Quick Charge
- ◆ 12V, 9Ah sealed lead acid maintenance free battery
- Easy to install and easy to handle
- Small, light weight, compact and maintenance free
- Adequate backup even for high end PC
- ❷ Back-up Time: 15-20 mins
- Automatic Voltage Regulation
- Protection: Fuse Protection / Noise Filter
- ✔ Full Safety from Short Circuit, Overload, Unsafe voltage levels etc.
- Wide Input Range (145~280VAC)
- 3 Indian Output Sockets
- Suitable for Indian Power Condition

#### 800-1200VA

Champion line interactive UPS series provides comprehensive protection for PC equipment. This is Plug n Play UPS designed to provide power protection for high performance computer systems, routers/modems, external storage devices, game consoles and other electronics in your home or business. The UPS is compact and comes with AVR (Automatic Voltage Regulation), so offers greater comprehensive power protection against surges and spikes / short circuit / overload / unsafe voltage levels, etc. The UPS will continue providing stable power to connected equipment and enable to shutdown PC safely during a power failure. It is a perfect choice for any home or small office application.













### **SPECIFICATIONS**

MODEL	UPS-800	UPS-1200
Power Capacity	800VA	1200VA
Input		
Input Voltage	230VAC, Single Phase 3 Wire	
Input Voltage Range	145VAC to 280VAC	
Input Frequency	50Hz	
Input Frequency Range	47 to 53 Hz	
Output		
Output Voltage	230VAC, Single Phase	
Output Frequency	50Hz ± 1%	
Output Waveform	Stepped Approximation to Sine Wave	
Indicators		
AC Normal	Solid Green Indication	
Back-up	Flashing Red Indication	Solid Red Indication
Battery Low / Overload	Fast Blinking Red Indication	Solid Red Indication
Charging	Fast Green Indication	
Alarms		
AC Fail	Slow Buzzer Beeps	
Battery Low	Fast Buzzer Beeps	
Protections		
Overload on Mains	Mains Fuse	
Overload on Backup	UPS Shutdown	
Battery Deep Discharge	Battery Low Alarm followed by Shutdown	
Battery		
Туре	Sealed Lead Acid Maintenance Free	
Back-up Time (Typical)	15 ~ 20 mins	
Rating	12V, 9Ah	24V, 9Ah (12V x 2)
Battery Recharge Time	5 ~ 8 hours	
General		
Noise Level	< 45 dB	
Operating Temperature	0° C − 45° C	
Physical		
Dimension (L×W×H) (mm)	305x100x145	370x125x195
Weight	5 kgs	10 kgs

 $<sup>\</sup>ensuremath{^*}$  Specifications are subject to change without notice.





mktgsupport@championups.com

www.championups.com

+91-9158897682

